

Specification Highlight

Item	NV7240		NV7480		NV7240 + NV7480
Operating System	Windows XP/ Vista				
Interface	PCI				
Video Compression	Hardware Compression				
Video Format	MPEG4				
Video Resolution (full de-interlace filter)	NTSC:352x240,720x240, 720x480 PAL:352x288, 720x288, 720x576				
Video Card (stackable structure)	NV7240 X1	NV7240 X2	NV7480 X1	NV7480 X2	NV7240 X1 + NV7480 X1
Video Input	8	16	16	32	24
Audio Input/ Output	4/1	8/1	4/1	8/1	8/1
Sensor Input/ Relay Out	4/4	8/8	4/4	8/8	8/8
Display Frame Rate (NTSC/PAL)	480/400 fps (D1)		960/800 fps (D1)		720/600 fps (D1)
Recording Frame Rate (NTSC/PAL)	240/200 fps (CIF) 120/100 fps (D1)	480/400 fps (CIF) 240/200 fps (D1)	480/400 fps (CIF) 120/100 fps (D1)	960/800 fps (CIF) 240/200 fps (D1)	720/600 fps (CIF) 240/200 fps (D1)
IP cam Support	AXIS, SONY, Panasonic, Arecont, Mobotix, BOSCH, Iqinvision, JVC, TOSHIBA, VIVOTEK, ACTI, D-Link, PIXORD, PELCO, Apron, Ilin and more				
Remote Access	CMS, Remote Console, WebViewer, PDAViewer, HandyViewer, JavaViewer, SmartViewer, IDispatch, etc				
TV output	Auto scan/ Alarm TV out				
Dimensions	165(W) x 105(D) mm				

Application Diagram

