



JNC-2613M / JNC-DN2613M

2 Megapixel IP Box Camera

Features

- 2 Mega-Pixel CMOS sensor
- H.264/ MJPEG/ MPEG4 Triple mode & streaming
- Support SD card for event recording
- Support DC IRIS
- 2-way audio / 1 Analog video output
- Digital I/O: 1 in/ 1 Relay out
- 3GPP for monitoring via 3G mobile phone
- IR-cut Filter Removable(JNC-DN2613M)



Specification

Camera	
Image Device	1/3" CMOS, 2 Mega-Pixels
Effective Pixels	1600x1200
Sensitivity	0.5 lux
Lens	Fixed Lens 4 mm, Mega Pixel
Day/ Night	Optional Mechanism IR Cut Filter (ICR)
DC IRIS	Support
Video Out	1 Analog video out (BNC connector)
Lens Changeable	Yes, CS Mount
Video	
Video Encoder	H.264 / MJPEG / MPEG-4 (3GPP only)
Video Resolution	1600x1200, 1280x1024, 1280x960, 1280x720, 800x592, 640x480, 320x240, 176x144
Image Frame Rate	Up to 15 FPS@1600x1200 ; Up to 30 FPS@1280x720
Video Bitrate Adjust	CBR, VBR
Video Adjust	Night Mode, Brightness, Contrast, BLC, Sharpness
Streaming	2 for live view, 1 for 3GPP
Audio	
Audio Streaming	Two-way
Microphone	Built-in microphone
Audio Output	1 Line out (RCA connector)
Network	
Supported Protocols	HTTP, TCP/IP, RTP/RTSP, 3GPP, NTP, SMTP, FTP, PPPoE, DHCP, DDNS, UPnP
Security	Password protection
Users	Up to 10 clients simultaneously
Ethernet	10/ 100 Base-T
Wireless	802.11b/g (optional) WEP, WPA-PSK, WPA2-PSK



System Integration	
Motion Detection	Yes, 3 different areas
Event Trigger	Motion Detection, Sensor In
Trigger Actions	Send Email, Send to FTP, Save to SD Card, Relay Out
Video Buffer	Pre- and post- alarm buffering
General	
RAM	256MB
ROM	16MB
Power Supply	DC 12V, 1A
Power over Ethernet	IEEE 802.3af (optional)
Digital I/O	1 In / 1 Relay out
Dimensions	W58 x H65 x D131.5 mm
Viewing System	
OS	Windows XP / Vista / Win 7
Browser	IE7,IE8, FireFox, Safari, Chrome, Opera
Cell Phone	With 3GPP player
Software	
Bundled NVR Program	Bundled with 36-Ch. Video Management Software
Optional NVR Program	4/9/16/36/72CH Profession Version of Video Management Application Software