



JNC-V2428ME

Megapixel Outdoor IP 20M IR Camera

Features

- 1.3 Mega-Pixel CMOS Sensor
- MPEG4 / MJPEG Dual streaming
- 3GPP for monitoring via 3G mobile phone
- 10FPS@1280x1024, 30FPS@640x480
- IR distance up to 20 meters
- Vari-focal Lens 2.8 ~ 10 mm
- IP66 waterproof standard
- Embedded PoE

Specification

Camera

Image Device	1.3 Mega-Pixel CMOS Sensor
Sensitivity	Normal: 0.1 lux, IR On: 0 lux
Lens	Vari-focal Auto Iris 2.8 ~ 10 mm, F1.6
Infrared LED	850nm LED
IR Distance	20 Meters

Video

Video Encoder	MPEG-4 / MJPEG
Video Resolution	1280x1024, 640x480 320x240, 160x120
Frame Rate	10FPS@1280x1024, 30FPS@640x480
Video Adjust	Brightness, Contrast, Exposure, Sharpness
Video Bitrate Adjust	CBR, VBR
Dual Streaming	Yes
Image Snapshot	Yes

Audio

Audio Streaming	---
Audio In/	---
Audio Output	---

Network

Supported Protocols	HTTP, TCP/IP, RTP/RTSP, 3GPP, NTP, SMTP, FTP, PPPoE, DHCP, DDNS, UPnP
Security	Password protection
Users	Up to 10 clients simultaneously
Ethernet	10/100M auto negotiation
3GPP	Live view with 3G mobile phone



System Integration	
Trigger Actions	Send Email, Send to FTP, Digital Out
Motion Detection	3 different areas
Pre/ Post Alarm	Yes, configurable
Firmware Upgrade	HTTP mode, remotely
General	
RAM	64MB
ROM	8MB
Power Supply	DC 12V, 1A, PoE
Power over Ethernet	Embedded PoE Splitter
Connectors	
Protect Standard	IP-66 standard
Dimension	W83 x H79.5 x L182.5 mm
Viewing System	
OS	Windows® 2000, XP, 2003
Browser	IE 6.0 or latter
Cell Phone	With 3GPP player
Software	
Search & Installation	IP Search
Bundled NVR Program	36-CH Video Mangement Software
Optional NVR Program	Professional 4-CH Video Mangement Software Professional 9-CH Video Mangement Software Professional 16-CH Video Mangement Software Professional 36-CH Video Mangement Software Professional 72-CH Video Mangement Software