

# H.264/MPEG4/MJPEG CMOS IP Camera

**JNC-V2619E**

**JNC-VIR2619E**

2.0 Megapixel IP Vandalproof Dome

Optional



POE Inject



## Features

- 2.0 Mega-Pixel CMOS Sensor
- H.264/MPEG4 / MJPEG Triple codec compression
- H.264/MPEG4 / MJPEG Triple streaming
- IR distance up to 12 meters
- 2-way audio
- 3GPP for monitoring via 3G mobile phone
- Support SD card for local record
- IP-66 Water Proof standard
- Embedded PoE
- Bundled with 36-Ch. Basic Version of Video Management Software (VMS)

## Specification

Model	JNC-V2619E	JNC-VIR2619E
CPU	ARM 9 ,32 bit RISC	
RAM	128MB	
ROM	8MB	
Image Sensor	1/3" CMOS, 2.0 Mega pixels	
Lens	Vari-focal 2.7 ~ 9 mm	
Frame Rate	Up to 15 FPS@1600x1200, Up to 30 FPS@800x600	
Water Proof Standard	IP66	
Digital I/O	1 in, 1 out	
Audio In/Out	1 Line in / 1 Line out (RCA connectors)	
Sensitivity	Normal: 1.5 lux, IR On: 0 lux	
Infrared LED	-	12M IR Distance
OS	Windows 2000, XP, 2003, IE6.0	
Suggested	Intel-C 1.6G, RAM: 1024MB, Graphic card: 128MB	
Minimum	Intel-C 1.6G, RAM: 256MB, Graphic card: 32MB	
Recording Trigger	Motion Detection, Sensor In, IP Check, Network Disconnect	
Trigger Actions	Send Email, Send to FTP, Digital out	
Video Resolution	1600x1200, 1280x1024, 1280x960, 1280x720, 800x600, 640x480,	
Video Adjust	Brightness, Contrast, Sharpness, BLC, Night Mode	
Motion Detection	Yes, 3 different areas	
Video Bitrate Adjust	CBR, VBR	
Triple Streaming	Yes	
Compression Format	H.264 / MJPEG / MPEG-4 (3GPP only)	
Pre/ Post Alarm	Yes, configurable	
Security	Password protection	
Firmware Upgrade	HTTP mode, can be upgraded remotely	
Simultaneous Connection	Up to 10	
Audio	Yes, 2-way	
Ethernet	10/ 100 Base-T	
Network Protocol	HTTP, TCP/IP, RTP/RTSP, 3GPP, NTP SMTP, FTP, PPPoE, DHCP, DDNS, UPnP	
3GPP	Yes, Live view with 3G mobile phone	
Video Format	AVI, JPEG	
Power Supply	138mm(Dia) x 105mm(H)	
Power Supply	DC 12V / 1A	